


CSLRG Series



Capacity:

50-1,600 ton

Stroke:

50-300 mm

Maximum Operating Pressure:

700 bar

CSLRG 液壓雙動，高噸位千斤頂

- CSLRG系列均具底座螺孔。
- 雙動推、拉液壓回縮。
- 主軸硬鉻處理，耐磨、抗腐蝕。
- 油壓缸的回油油路具回油安全閥裝置預防突然超壓損害。
- 可替換式的溝槽墊塊為標準配件。
- 防塵環減少污染物附著。
- 表面粉體塗裝美觀抗腐蝕、防銹。
- 各型號均含SQB-3/8UF快速接頭及防塵蓋。

Double-Acting, High Tonnage Cylinders

- ※Base mounting holes standard on all models.
- ※Double-acting, for push and pull.
- ※Hard chrome plated plunger resists wear and corrosion.
- ※Safety valve in retract side of cylinder helps to prevent damage in case of accidental over-pressurization.
- ※Interchangeable, hardened grooved saddles are standard.
- ※Plunger wiper reduces contamination, extending cylinder life.
- ※Powder coat finish for increased corrosion resistance and antirust.
- ※Come with SQB-3/8UF female coupler & dust cap.



墊塊/鞍座 Saddle

- CSLRG-系列 均配有高硬度可移除式溝槽墊塊於起重時具防滑作用。偏心起重時請選用傾斜墊塊。
- 選配之傾斜墊塊請參閱選擇對照資訊。



- ※ CSLRG-Series are equipped with hardened removable "Ribbed saddles" to prevent slippage during jacking.
- For off-center loading application, see optional tilting saddle.
- ※ For information on optional tilt saddles, see selection chart.



液壓泵浦 Pump Selection

雙動液壓千斤頂必須搭配具 4 口閥門的液壓泵浦。

A double-acting cylinder must be powered by a pump with a 4-way valve.

油壓缸能力選擇 Cylinder Capacity

- 高於1000 噸以上油壓缸亦提供製造。
- 請將您在舉昇系統中所需要的協助和相關技術資訊與就近的SUN RUN服務中心取得連繫。



- ※ More above 1000 tons cylinder capacity are also available.
- ※ Please contact SUN RUN office nearest to you for advice and technical assistance in the layout of your ideal Lift System.



請勿調整安全閥壓力！

適用於雙動千斤頂

RSR, RSRH, CSLRG 系列大部份的雙動千斤頂安全閥壓力設定值為 10000psi(700bar)。

超出原廠設定值時，安全閥會噴出液壓油保護千斤頂。當安全閥發生漏油狀況時請先檢查快速接頭連接狀況。

Don't adjust safety valve pressure!


Apply to double-acting cylinder

RSR, RSRH, CSLRG series

Most double-acting cylinder safety valve pressure setting 10000psi(700bar).

As surpasses the original factory hypothesis pressure safety valve will spurt oil to protect cylinder.

Leaking from safety valve, inspect connection of coupler at first.



底座螺孔方位

Mounting Hole Direction


- 上方底座螺孔依據油孔位置設定方位。
- 下方底座螺孔則依本廠設計設定方位。
- ※ Top mounting hole orientation is maintained to port location.
- ※ Bases mounting hole orientation is not maintained to port location.





提把型式 Handle type	
(S) : 標準配件 standard equipped	
(O) : 選配 option	
● 焊提把 Weldable	
★ 吊環螺栓 Eyebolt	
▲ 活動提把 Removable strap handles	
■ 螺牙式活動提把 Thread	

	焊提把 Weldable
	吊環螺栓 Eyebolt
	活動提把 Removable strap handles
	螺牙式活動提把 Thread



選配說明

假如您需要選配其他要求於您所訂製的千斤頂/油壓缸上,請依下列規範字尾增加編號

油缸外牙: CT

主軸內牙: PT

油缸外牙+主軸內牙: CPT

案例:

CSLRG-502選配油缸外牙及主軸內牙,訂製型號改為CSLRG-502CPT
相關技術諮詢請與SUN RUN取得聯繫。

Opt Features

To add optional features to order cylinder, add follow suffixes to the end of the model No..

Collar Thread:CT

Plunger internal thread:PT

Collar Thread+

Plunger internal thread:CPT

Example:

CSLRG-502 with collar and plunger internal thread, order:CSLRG-502CPT.
Technical specifications for these features are available from SUN RUN.

提把型式 Handle type	型號 Model Number	外部尺寸 Outer Dimension						選配傾斜墊塊 Optional Tilt Saddle		
		能力 Cyl. Cap.	揚程 Stroke	最大出力 Max. Cylinder Cap.		本身高 Coll. Height	總重 Wt.	型號 Model Number	直徑 Diam.	高度 Ht.
				推 Push	拉 Pull					
(S)		ton(kN)	(mm)	(kN)		A (mm)	(kg)		J1 (mm)	K1 (mm)
★	CSLRG-502	50 (539)	50	539	269	162	17	XKCATG-50	50	24
★	CSLRG-504		100	539	269	212	20	XKCATG-50	50	24
★	CSLRG-506		150	539	269	262	23	XKCATG-50	50	24
★	CSLRG-508		200	539	269	312	27	XKCATG-50	50	24
★	CSLRG-5010		250	539	269	362	31	XKCATG-50	50	24
★	CSLRG-5012	100 (929)	300	539	269	412	34	XKCATG-50	50	24
★	CSLRG-1002		50	929	433	182	29	XKCATG-100	73	29
★	CSLRG-1004		100	929	433	232	34	XKCATG-100	73	29
★	CSLRG-1006		150	929	433	282	40	XKCATG-100	73	29
★	CSLRG-1008		200	929	433	332	46	XKCATG-100	73	29
★	CSLRG-10010	150 (1390)	250	929	433	382	52	XKCATG-100	73	29
★	CSLRG-10012		300	929	433	432	65	XKCATG-100	73	29
★	CSLRG-1502		50	1390	675	196	39	XKCATG-150	91	31
★	CSLRG-1504		100	1390	675	246	52	XKCATG-150	91	31
★	CSLRG-1506		150	1390	675	296	65	XKCATG-150	91	31
★	CSLRG-1508	200 (1861)	200	1390	675	346	78	XKCATG-150	91	31
★	CSLRG-15010		250	1390	675	396	92	XKCATG-150	91	31
★	CSLRG-15012		300	1390	675	446	105	XKCATG-150	91	31
★	CSLRG-2002	250 (2565)	50	1861	889	216	68	XKCATG-200	113	35
★	CSLRG-2006		150	1861	889	316	93	XKCATG-200	113	35
★	CSLRG-20012		300	1861	889	466	146	XKCATG-200	113	35
★	CSLRG-2502	300 (3193)	50	2565	1068	235	102	XKCATG-250	144	46
★	CSLRG-2506		150	2565	1068	335	136	XKCATG-250	144	46
★	CSLRG-25012		300	2565	1068	485	207	XKCATG-250	144	46
★	CSLRG-3002	400 (3919)	50	3193	1060	312	184	XKCATG-300	160	62
★	CSLRG-3006		150	3193	1060	412	232	XKCATG-300	160	62
★	CSLRG-30012		300	3193	1060	562	303	XKCATG-300	160	62
★	CSLRG-4002	500 (5114)	50	3919	1354	375	270	XKCATG-400	193	51
★	CSLRG-4006		150	3919	1354	475	330	XKCATG-400	193	51
★	CSLRG-40012		300	3919	1354	625	421	XKCATG-400	193	51
★	CSLRG-5002	600 (5987)	50	5114	1733	419	401	XKCATG-500	228	63
★	CSLRG-5006		150	5114	1733	519	480	XKCATG-500	228	63
★	CSLRG-50012		300	5114	1733	669	599	XKCATG-500	228	63
★	CSLRG-6002	800 (8234)	50	5987	2068	429	474	XKCATG-600	241	76
★	CSLRG-6006		150	5987	2068	529	565	XKCATG-600	241	76
★	CSLRG-60012		300	5987	2068	679	701	XKCATG-600	241	76
★	CSLRG-8002	1000 (10260)	50	8234	2709	474	741	XKCATG-800	287	75
★	CSLRG-8006		150	8234	2709	574	868	XKCATG-800	287	75
★	CSLRG-80012		300	8234	2709	724	1058	XKCATG-800	287	75
★	CSLRG-10002	1600 (16024)	50	10260	3792	564	1062	XKCATG-1000	311	93
★	CSLRG-10006		150	10260	3792	664	1213	XKCATG-1000	311	93
★	CSLRG-100012		300	10260	3792	814	1439	XKCATG-1000	311	93
★	CSLRG-16006		155	16024	4891	825	2179	XKCATG-1600	385	125

型號 Model Number	外部尺寸 Outer Dimension													
	場程 Stroke (mm)	最大出力 Max. Cylinder Cap. 推 Push 拉 Pull (kN)		受壓面積 Cylinder Effective Area 推 Push 拉 Pull (cm ²)		總油量 Oil Cap. 推 Push 拉 Pull (cm ³)		本身高 Coll. Height A (mm)	伸長總高 Ext. Height (mm)	外徑 Outside Diam. D (mm)	內徑 Cyl. Bore Diam. E (mm)	主軸直徑 Plunger Diam. F (mm)	底部前進 油孔位置 Base to Advance Port H (mm)	頂部回油 油孔位置 Top to Retract Port I (mm)
CSLRG-502	50	539	269	76.2	37.7	385	192	162	212	130	98.6	70.0	42	33
CSLRG-504	100	539	269	76.2	37.7	770	385	212	312	130	98.6	70.0	42	33
CSLRG-506	150	539	269	76.2	37.7	1155	577	262	412	130	98.6	70.0	42	33
CSLRG-508	200	539	269	76.2	37.7	1540	770	312	512	130	98.6	70.0	42	33
CSLRG-5010	250	539	269	76.2	37.7	1924	962	362	612	130	98.6	70.0	42	33
CSLRG-5012	300	539	269	76.2	37.7	2309	1155	412	712	130	98.6	70.0	42	33
CSLRG-1002	50	929	433	132.7	61.9	664	309	182	232	165	130.0	95.0	54	48
CSLRG-1004	100	929	433	132.7	61.9	1327	619	232	332	165	130.0	95.0	54	48
CSLRG-1006	150	929	433	132.7	61.9	1991	928	282	432	165	130.0	95.0	54	48
CSLRG-1008	200	929	433	132.7	61.9	2655	1237	332	532	165	130.0	95.0	54	48
CSLRG-10010	250	929	433	132.7	61.9	3318	1546	382	632	165	130.0	95.0	54	48
CSLRG-10012	300	929	433	132.7	61.9	3982	1856	432	732	165	130.0	95.0	54	48
CSLRG-1502	50	1390	675	198.6	96.5	993	482	196	246	205	159.0	114.0	61	56
CSLRG-1504	100	1390	675	198.6	96.5	1986	965	246	346	205	159.0	114.0	61	56
CSLRG-1506	150	1390	675	198.6	96.5	2978	1447	296	446	205	159.0	114.0	61	56
CSLRG-1508	200	1390	675	198.6	96.5	3971	1930	346	546	205	159.0	114.0	61	56
CSLRG-15010	250	1390	675	198.6	96.5	4964	2412	396	646	205	159.0	114.0	61	56
CSLRG-15012	300	1390	675	198.6	96.5	5957	2895	446	746	205	159.0	114.0	61	56
CSLRG-2002	50	1861	889	265.9	127.0	1330	635	216	266	235	184.0	133.1	67	56
CSLRG-2006	150	1861	889	265.9	127.0	3989	1905	316	466	235	184.0	133.1	67	56
CSLRG-20012	300	1861	889	265.9	127.0	7977	3809	466	766	235	184.0	133.1	67	56
CSLRG-2502	50	2565	1068	366.4	152.6	1832	763	235	285	275	216.0	165.1	73	78
CSLRG-2506	150	2565	1068	366.4	152.6	5497	2289	335	485	275	216.0	165.1	73	78
CSLRG-25012	300	2565	1068	366.4	152.6	10993	4578	485	785	275	216.0	165.1	73	78
CSLRG-3002	50	3193	1060	456.2	151.4	2281	757	312	362	310	241.0	197.1	101	75
CSLRG-3006	150	3193	1060	456.2	151.4	6843	2270	412	562	310	241.0	197.1	101	75
CSLRG-30012	300	3193	1060	456.2	151.4	13685	4541	562	862	310	241.0	197.1	101	75
CSLRG-4002	50	3919	1354	559.9	193.5	2800	967	375	425	350	267.0	216.0	114	105
CSLRG-4006	150	3919	1354	559.9	193.5	8399	2902	475	625	350	267.0	216.0	114	105
CSLRG-40012	300	3919	1354	559.9	193.5	16797	5804	625	925	350	267.0	216.0	114	105
CSLRG-5002	50	5114	1733	730.6	247.6	3653	1238	419	469	400	305.0	248.0	114	135
CSLRG-5006	150	5114	1733	730.6	247.6	10959	3713	519	669	400	305.0	248.0	114	135
CSLRG-50012	300	5114	1733	730.6	247.6	21918	7427	669	969	400	305.0	248.0	114	135
CSLRG-6002	50	5987	2068	855.3	295.4	4276	1477	429	479	430	330.0	267.0	114	135
CSLRG-6006	150	5987	2068	855.3	295.4	12829	4431	529	679	430	330.0	267.0	114	135
CSLRG-60012	300	5987	2068	855.3	295.4	25659	8862	679	979	430	330.0	267.0	114	135
CSLRG-8002	50	8234	2709	1176.3	387.0	5881	1935	474	524	505	387.0	317.0	149	135
CSLRG-8006	150	8234	2709	1176.3	387.0	17644	5806	574	724	505	387.0	317.0	149	135
CSLRG-80012	300	8234	2709	1176.3	387.0	35288	11611	724	1024	505	387.0	317.0	149	135
CSLRG-10002	50	10160	3699	1451.5	528.5	7329	2709	564	614	560	430.0	343.0	174	170
CSLRG-10006	150	10160	3699	1451.5	528.5	21986	8126	664	814	560	430.0	343.0	174	170
CSLRG-100012	300	10160	3699	1451.5	528.5	43972	16252	814	1114	560	430.0	343.0	174	170
CSLRG-16006	155	16024	4891	2289.1	699.3	35495	10845	825	980	710	540.0	450.0	205	170

型號 Model Number	外部尺寸 Outer Dimension				底座螺孔 Base Mounting Hole Dimensions		
	墊塊直徑 Standard Saddle Diam.	凸出高度 Saddle Protrusion from Plngr.	主軸孔 深度 Depth of Plunger Hole	總重 Wt.	底座孔距 Bolt Cir. Diam.	底座螺紋 Thread	螺紋深度 Thread Depth
	J (mm)	K (mm)	L (mm)	(kg)	U (mm)	V (mm)	Z (mm)
CSLRG-502	50	1	19	17	65	M12	22
CSLRG-504	50	1	19	20	65	M12	22
CSLRG-506	50	1	19	23	65	M12	22
CSLRG-508	50	1	19	27	65	M12	22
CSLRG-5010	50	1	19	31	65	M12	22
CSLRG-5012	50	1	19	34	65	M12	22
CSLRG-1002	75	1	19	29	95	M12	22
CSLRG-1004	75	1	19	34	95	M12	22
CSLRG-1006	75	1	19	40	95	M12	22
CSLRG-1008	75	1	19	46	95	M12	22
CSLRG-10010	75	1	19	52	95	M12	22
CSLRG-10012	75	1	19	65	95	M12	22
CSLRG-1502	94	1	19	39	130	M12	22
CSLRG-1504	94	1	19	52	130	M12	22
CSLRG-1506	94	1	19	65	130	M12	22
CSLRG-1508	94	1	19	78	130	M12	22
CSLRG-15010	94	1	19	92	130	M12	22
CSLRG-15012	94	1	19	105	130	M12	22
CSLRG-2002	113	1	24	68	165	M12	22
CSLRG-2006	113	1	24	93	165	M12	22
CSLRG-20012	113	1	24	146	165	M12	22
CSLRG-2502	145	1	24	102	190	M12	22
CSLRG-2506	145	1	24	136	190	M12	22
CSLRG-25012	145	1	24	207	190	M12	22
CSLRG-3002	177	1	19	184	180	M16	36
CSLRG-3006	177	1	19	232	180	M16	36
CSLRG-30012	177	1	19	303	180	M16	36
CSLRG-4002	196	3	27	270	205	M16	36
CSLRG-4006	196	3	27	330	205	M16	36
CSLRG-40012	196	3	27	421	205	M16	36
CSLRG-5002	228	3	27	401	250	M24	38
CSLRG-5006	228	3	27	480	250	M24	38
CSLRG-50012	228	3	27	599	250	M24	38
CSLRG-6002	247	3	27	474	275	M24	38
CSLRG-6006	247	3	27	565	275	M24	38
CSLRG-60012	247	3	27	701	275	M24	38
CSLRG-8002	297	3	27	741	330	M24	38
CSLRG-8006	297	3	27	868	330	M24	38
CSLRG-80012	297	3	27	1058	330	M24	38
CSLRG-10002	323	3	27	1062	375	M24	38
CSLRG-10006	323	3	27	1213	375	M24	38
CSLRG-100012	323	3	27	1439	375	M24	38
CSLRG-16006	—	—	—	2179	400	M24	30

